

Appl. No. 09/607,790
Amdt. Dated December 13, 2004
Reply to Office action of October 22, 2004
Attorney Docket No. P12172-US2
EUS/J/P/04-3309

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of setting up a call in a wireless communication network comprising:

receiving a service request for a call[[,]] at one of a plurality of control nodes in the wireless communication network, wherein the network is a Narrowband Integrated Services Digital Network (N-ISDN) and call control and bearer control are separated, the call being intended for a select destination:

selecting at least one media gateway to switch a user plane for handling the call depending on one of origin of the call, destination of the call and required service of the call, the at least one MGW including plural logical points for connecting plural MGW resources for handling the user plane of the call, the at least one MGW being adapted to identify one of the logical points to one of the control nodes in response to a request for resources from the one of the plurality of control nodes;

reserving a logical point in said at least one media gateway and
communicating with the media gateway to setup bearer control for the call.

2. (Original) The method of claim 1 wherein the call is from a mobile terminal in the network to a mobile terminal in the network and the selecting step comprises a single media gateway for handling the call.

3. (Original) The method of claim 1 wherein the call is from external to the network to a mobile terminal in the network and the selecting step comprises selecting a single media gateway for handling the call.

4. (Original) The method of claim 1 wherein the call is from external to the network and the select destination is external to the network and the selecting step

Appl. No. 09/607,790
Amdt. Dated December 13, 2004
Reply to Office action of October 22, 2004
Attorney Docket No. P12172-US2
EUS/J/P/04-3309

comprises selecting a first media gateway and a second media gateway for handling the call.

5. (Original) The method of claim 1 wherein the media gateway is selected from among a plurality of media gateways dependent on media gateway capabilities required for handling the call control node

6. (Original) The method of claim 1 wherein the media gateway is selected from among a plurality of media gateways dependent on a selected destination for the call.

7. (Original) The method of claim 1 wherein the call is from a mobile terminal in the network to external to the network and the selecting step comprises selecting a single media gateway for handling the call.

8. (Original) The method of claim 1 wherein the selecting step comprises selecting a group of MGWs according to the select destination of the call and the at least one MGW is selected from the group of MGWs according to capabilities of the at least one MGW.

9. (Original) The method of claim 8 wherein the at least one MGW is further selected based on traffic load of the at least one MGW.

10. (Original) The method of claim 1 wherein an MPTY call is established by selecting an MGW preferring the MGW serving the active call, and if said MGW serving the active call cannot be used, the MGW serving the held call, and if the MGW serving the held call cannot be used, an MGW with MPTY capabilities selected based on traffic conditions.

App. No. 09/507,790
Amdt. Dated December 13, 2004
Reply to Office action of October 22, 2004
Attorney Docket No. P12172-US2
EUS/J/P/04-3309

11. (Currently Amended) A method of setting up a call in a wireless communication network comprising:

a) initiating call setup over one control node, the one control node determining a media gateway (MGW) for routing a user plane of the call, wherein the determination of the MGW is made depending on one of: origin of the call, destination of the call and required service of the call, the MGW including plural logical points for connecting plural MGW resources for handling the user plane of the call, the MGW being adapted to identify one of the logical points to one of the control nodes in response to a request for resources from the one of the plurality of control nodes;

b) the one control node requesting resources from the MGW for handling the call and reserving a logical point in the media gateway;

c) the one control node transferring an address for the MGW in a forward direction to a further control node; and

(d) the further control node implementing steps b) and c) until either a call destination or an external network is reached, the call being carried through the wireless communications network, wherein the wireless communications network is a Narrowband Integrated Services Digital Network (N-ISDN) whereby call control is implemented in the control nodes and bearer control is implemented in the MGW.

12. (Original) The method of claim 11 wherein the one control node selects the MGW for handling the bearer control of the call.

13. (Original) The method of claim 11 wherein the further control node is a gateway MSC.

14. (Original) The method of claim 11 wherein the further control nodes are a gateway MSC and a second MSC.

15. (Original) The method of claim 11 wherein the one control node is a Transit Switching Center.

Appl No 09/607,790
Amdt. Dated December 13, 2004
Reply to Office action of October 22, 2004
Attorney Docket No. P12172-US2
EUS/J/P/04-3309

16. (Original) The method of claim 11 wherein the MGW reserves a logical point identifying reserved resources in the MGW for handling the call in response to a request for resources.

17. (Original) The method of claim 16 wherein the step c), the one control node transferring an address for the MGW in a forward direction to a further control node, further comprises transferring an identification of the logical point in the forward direction to the further control node.

18. (Currently Amended) A wireless communication network comprising:
a plurality of control nodes, the control nodes receiving information about a call, the control nodes requesting resources from at least one media gateway (MGW) for handling a user plane of the call, wherein the wireless communication network is a Narrowband Integrated Services Digital Network (N-ISDN) and the selection of the at least one MGW depends on one of origin of the call, destination of the call or required service of the call; and

the at least one MGW including plural logical points for connecting plural MGW resources for handling the user plane of the call, the at least one MGW being adapted to identify one of the logical points to one of the control nodes in response to a request for resources from the one of the control nodes,

whereby the ~~plural~~ plurality of control nodes use the at least one MGW for handling the user plane of the call.

19. (Original) The wireless communication network of claim 18 wherein at least one of the plural MGW resources is one of a transcoder, a conference call device, a modem, a tone generator, a framing device or an announcement device.

20. (Original) The wireless communication network of claim 18 wherein the communication between control nodes and the at least one MGW regarding the control

Appl. No. 09/607,790
Amdt. Dated December 13, 2004
Reply to Office action of October 22, 2004
Attorney Docket No. P12172-US2
EUS/JIP/04-3309

and reservation of resources in said at least one MGW is performed using a Device Control Protocol.

21. (Original) The wireless communication network of claim 20 wherein the Device Control Protocol is H.GCP.

22. (Original) The wireless communication network of claim 18 wherein the control nodes request resources from one of the MGWs in response to the information being a service request for the call.

23. (Original) The wireless communication network of claim 22 wherein each MGW includes plural logical points for connecting plural MGW resources for handling the call, the MGW being adapted to identify one of the logical points to one of the control nodes in response to a request for resources from the one of the control nodes.

24. (Original) The wireless communication network of claim 23 wherein the identified logical point identifies a reserved resource and is returned to the control server using H.GCP.

25. (Original) The wireless communication network of claim 18 wherein the network uses an N-ISUP interface between the control nodes for call control signaling.

26. (Original) The wireless communication network of claim 18 wherein the user plane is transferred compressed within and between MGWs.

27. (Currently Amended) A wireless communication network comprising:
at least one media gateway (MGW), each MGW being adapted for routing a user plane of a call and each MGW including MGW resources for handling the call, the at least one media gateway including a plurality of logical points for connecting plural

Appl. No. 09/807,790
Amdt. Dated December 13, 2004
Reply to Office action of October 22, 2004
Attorney Docket No. P12172-US2
EUS/J/P/04-3309

MGW resources for handling the user plane of the call and the MGW being adapted to identify one of the logical points in response to a request from one of at least one control nodes, wherein the wireless communication network is a Narrowband Integrated Services Digital Network (N-ISDN); and

~~at least one control node~~, the at least one control node adapted for implementing application logic for call control and for reserving at least one of the plurality of logical points in the MGW for handling the user plane, the application logic requesting MGW resources from the at least one MGW for handling a call to allow pooling of MGW resources under control of the application logic,

wherein the at least one MGW is selected by the at least one control node utilizing at least one of: call origin, call destination, required service of the call or framing of the call.

28. (Original) The wireless communication network of claim 27 further comprising an interface for signaling for MGW control between the at least one MGW and the at least one control node.